



## Glossary of Common Terms

- Adjustable Insertion Force** - Adjustability in the force required to install the mating connector\PCB.
- Adjustable Row Spacing** - Adjustability in the distance between the pins located within the same position of an edgecard.
- Back Up Springs** - Contacts on an unused side of a connector that act as springs to maintain acceptable insertion/withdrawal forces.
- Bi-Level** - A connector containing two staggered levels of contacts, creating a double density connector.
- Cantilever** - A contact style where there is only one flex point.
- Card Edge** - A connector that acts as the mechanical interface between the mother and daughter cards, in a multi-board assembly.
- Card Extender Termination** - A termination style where the contacts straddle the motherboard on both sides.
- Card Slot** - The part of an edgecard connector that the daughter card is plugged into.
- Connector** - A device that is used to achieve electrical connections between other devices, such as circuit boards.
- Contact** - The pin enclosed in a connector that carries the electrical signal.
- Contact Area** - The area of the pin that makes contact with the mating connector\PCB.
- Contact Center** - The distance between contacts on a connector, as measured from center to center.
- Contact Material** - The base material of the contact, determining conductivity, flexibility, stress relaxation, and other characteristics.
- Contact Point** - The point of a contact that makes physical connection with the mating connector\PCB.
- Cycle Rating** - The number of times a daughter card can be inserted and withdrawn without failure of the edgecard.
- Daughter Card** - The circuit board that is plugged into the cardslot side of an edgecard connector.
- Dip Solder Termination** - A termination style where the contacts dip straight through the motherboard for easy soldering.
- Dual Row** - Containing two rows of pins.
- Edgecard** - A connector that acts as the mechanical interface between the mother and daughter cards, in a multi-board assembly.
- Eyelet Contacts** - A type of termination where the pin has a hole through it for the purpose of soldering a wire to the contact.
- Full Loop Contacts** - A contact type where the head of the contact loops around in a manner that the pin has three flexing points.
- Hairpin Contacts** - A contact type where the head has one loop over the top and comes down.
- Half Load** - Edgecard where only one row of pins are loaded. Typically used for one-sided daughter cards.
- Header** - A connector style that consists of one or two rows of contacts (male) or sockets (Female)
- High Cycle** - Withstanding a large number of mating cycles (usually 500 or more) without failure.
- High Density** - Having a small pin pitch, with contacts very close together (usually .050" or closer).
- High Profile** - Having a tall overall height (usually indicates .710")
- High Temp** - Withstanding continuous operating temperatures of 150°C or higher
- Injection Molding** - The method where molten plastic is pushed into a mold and cooled to form a solid connector housing.
- Insertion Force** - The amount of force (usually in ounces) it takes to insert a daughter card or mating connector into an edgecard.
- Insulator** - The plastic connector housing, which holds and insulates the contacts. Material depends on application requirements.
- Lead Time** - The length of time between when an order is placed to when it is shipped.



## Glossary of Common Terms

**Low Insertion Force** - The force required to install the mating connector\PCB is lower than normal.

**Low Profile** - Having a low overall height (usually indicates .431”).

**Mold Tooling** - The individual pieces of steel that make up the mold.

**Mold** - The complete steel tool that the molten plastic is injected into, to create the connector housing.

**Molded Key** - A plastic divider in the card slot. Commonly used to ensure the daughtercard can be installed in only one direction.

**Mounting Styles** - The various options to mount the connector to the PCB; also known as “mounting ears”.

**Nickel Under Plating** - The first plating layer (nickel) protects from corrosion, contamination and improves gold plating adhesion.

**Open Cardslot** - A card slot with no walls at either end. Commonly used to accommodate PCBs with a long flat edge.

**Part Marking** - The application of ink to the edgecard to identify its part number and lot code.

**PCB** - Printed Circuit Board. A flat plastic or fiberglass board on which integrated circuits and other components are attached.

**Plating** - The coating applied over the base contact material that protects from corrosion and contamination.

**Position** - The number of “sets” of contacts in an edgecard connector.

**Press Fit** - A contact shape that provides an interference fit with the PCB, eliminating the need to solder the connection.

**Private Label** - Part marking with customer label instead of manufacturer label, under special permission.

**Right Angle Termination** - A termination style where the contacts are bent at a 90° angle.

**Row Spacing** - The distance between the contacts, located within the same position of an edgecard connector.

**Seater** - A piece of production tooling that is used to set the pins in their proper position during the assembly procedures.

**Selective Plating** - Plating the contact area or head of a contact with gold, and the tail section (soldered side) with tin.

**Single Row** - When two rows of contact tails are bent to form a single row, on the termination side of an edgecard connector.

**Surface Mount** - A termination style that allows the connector to be soldered to the PCB on it’s surface, with no holes in the PCB.

**Tail Length** - The distance from the bottom of the insulator body (FB) or the insulator standoffs (FS) to the tips of the contact tails.

**Termination** - The shape of the contact on the tail side.

**Tooling** - The tools that are used to mold, assemble, or shape a connector.

**Traceability** - The ability to track an individual part from raw material all the way to the customer, or the other way around.

**Wire Wrap Termination** - A termination style where the tails are long and square, ideal for wrapping and soldering wire around.

**Withdrawal Force** - The amount of force that is required to remove a daughter card from the card slot of an edgecard connector.